


# BATTERYstart

12V Lithium Starter\*

**BATTERYstart 700 PRO**




BATTERYstart 700 PRO	
	12V / ≤ 8.0L Petrol, ≤ 6.0L Diesel
	24.000mAh (76.8Wh) – 6Ah per cell, 12.8V, LiFePO4
[A]	a: 650A / b: 1500A
	Cu (20mm <sup>2</sup> )
	3.0V – 15.0V
	<3.0V
	0°C...45°C
	4kg



**OSRAM**

## Warnings\*\*

- 1) During charging of the jumpstarter it should be placed in a well-ventilated area.
- 2) The battery terminal not connected to the chassis has to be connected first. The other connection is to be made to the chassis, remote from the battery and fuel line.
- 3) After Jumpstarting remove the chassis connection and then the battery connection.
- 4) The appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction.
- 5) Children being supervised not to play with the appliance.
- 6) The appliance is only to be used with the unit provided and it must only be supplied at SELV (Safety extra-low voltage).
- 7) The connection to the supply mains is to be in accordance with the national wiring rules.
- 8) This appliance contains batteries that are non-replaceable.
- 9) For the purposes of recharging the battery, only use the detachable supply unit provided with this appliance.



IEC 60417-5957

(2004-12)


(for indoor use only)



IEC 60417-6062

(2011-05)

(do not expose to moisture)







IEC 60417-6181

(2013-03)




(detachable supply unit)

## BATTERYstart 700 PRO





# BATTERYstart 700 PRO



# BATTERYstart 700 PRO

