

BATTERYcharge 908



Start/Stop compatible

Protects batteries in cold temperatures



Winter mode

Protects batteries in cold temperatures



9-stage charging cycle

For easy charging of Lead Acid/AGM batteries



Smart battery charger and maintainer with multi-stage charging cycle

The OSRAM BatteryCharger 908 is a 8A smart charger and battery maintainer for 12V and 24V vehicles including most cars, vans and small trucks. Maintains and charges a vehicle's battery through a 7 stage charging cycle at the touch of a button for Lithium batteries, with only a 9-stage cycle of Lead Acid/AGM batteries. Includes a backlit LCD digital display to keep things easy even in low light. A host of safety features including reverse polarity and short-circuit protection, keeps both the user and the vehicle safe. Be sure that the charger is maintaining your car battery as it automatically changes to long-term maintenance mode when the vehicle's battery is full.


Product datasheet

Technical data

Electrical data

Charge Rate (Up to)	8.0 A
Maintenance Charge (up to)	4.0 A
Max battery size for charging 12V	150 Ah
Max battery size for charging 24V	70 Ah

Dimensions & weight



Length	185.0 mm
Width	106.0 mm
Height	70.0 mm
Power Cable Length	1.5 m
Clamps Cable Length	1.5 m
Construction length	0.0

Additional product data

Recommended to Use With	Motorcycle, Car, SUV, Van, Small Truck
Stages: Lead, AGM, EFB	9
Stages: Lithium	7
Battery Connection	O-rings, Crocodile Clamps

Product datasheet



Detail



Detail






Detail

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899620544	BATTERY charge 908	Folding carton box 1	145 mm x 128 mm x 272 mm	5.05 dm ³	1041.00 g
4052899620629	BATTERY charge 908	Shipping carton box 4	314 mm x 280 mm x 334 mm	29.37 dm ³	4740.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction BATTERYcharge
 Movie application BatteryCharge How to Video (EN)
 Product movie OSRAM BATTERYcharge OEBCS908 Product Video (EN)

Legal advice

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice:

For more detailed application information and graphics please see product datasheet.

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.