

GB

Safety data sheet according to 1907/2006/EC, Article 31 Printing date 02.06.2015 Version number 51 Revision: 02.06.2015 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: MOTIP BITUMEN BASED UNDERCOATING · Article number: 000016 (1.300 gr.) / 000173 (2.500 gr.) · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Anticorrosion additive \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com · Further information obtainable from: QHSE Department · 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS08 health hazard STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · Classification according to Directive 67/548/EEC or Directive 1999/45/EC *R10-52/53-66-67*: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotising effect. Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. (Contd. on page 2) Page 2/9


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING



· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

(Contd. on page 3)

Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

CAS (4742.05.(. of page
CAS: 64742-95-6 EC number: 918-668-5	Solvent naphtha (petroleum), light arom.	5-10%
	Xn R65	
Reg.nr.: 01-2119455851-35-xxxx		
	N R51/53 R10-66-67	
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 	
	Aquatic Chronic 2, H411	
	STOT SE 3, H335-H336	
CAG (4742.02.1		5 100
CAS: 64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics	5-10%
<i>EC number: 919-446-0</i>	(2-25%)	
Reg.nr.: 01-2119458049-33-xxxx		
	N R51/53 R10-66-67	
	Carc. Cat. 2	
	 Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 	
	Aquatic Chronic 2, H411	
	STOT SE 3, H336	
CAS: 64742-48-9		5-10%
EC number: 919-857-5	<i>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics</i>	3-10%
Reg.nr.: 01-2119463258-33-xxxx		
Reg.nr.: 01-2119405258-55-xxxx	R10-66-67	
	The second secon	
	Asp. Tox. 1, H304	
	STOT SE 3, H336	
CAS: 67-56-1	methanol	0.1-19
EINECS: 200-659-6	$\square T R23/24/25-39/23/24/25$	0.1-17
Index number: 603-001-00-X	F R11	
Reg.nr.: 01-2119433307-44-xxxx		
Педани. 01-211/45550/ -44-халл	\sim Fiam. Eq. 2, E225 Acute Tox 3 H301 · Acute Tox 3 H311 · Acute Tox 3 H331	
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 wording of the listed risk phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

GB

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:	· Ingredients with	limit values that	require monitoring	at the workplace:
---	--------------------	-------------------	--------------------	-------------------

67-56-1 methanol

- WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk
- Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

(Contd. of page 4)

Trade name: MOTIP BITUMEN BASED UNDERCOATING

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Not required.

· Penetration time of glove material Not required.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

General Information Appearance:	
Form:	Pasty
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	130 °C (266 °F)
Flash point:	39 °C (102 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C (> 392 °F)
	200 °C (392 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/
	vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
	0.6 %
Upper:	8.0 Vol %
	7.0 %
Vapour pressure at 20 °C (68 °F):	30 hPa (23 mm Hg)
• • • • • • •	2 hPa (2 mm Hg)
Density at 20 °C (68 °F):	1.28 g/cm ³ (10.682 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	r): Not determined.
Viscosity:	
<i>Dynamic at 20 °C (68 °F):</i>	17000 mPas
Kinematic:	Not determined.

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

		(Contd. of page 5)
 Solvent content: Organic solvents: EU-VOC: EU-VOC in %: 	24.7 % 316.2 g/l 24.70 %	
• Solids content: • 9.2 Other information	75.3 % No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

 \cdot 10.4 Conditions to avoid No further relevant information available.

 \cdot 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

		• •	
64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	3592 mg/kg (rat) (OECD401)	
Dermal	LD50	>3160 mg/kg (rab) (OECD402)	
Inhalative	LC50 / 4 h	>6193 mg/m3 (rat)	
64742-82-	64742-82-1 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	3400 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	13100 mg/m3 (rat)	
64742-48-	9 Hydrocarl	bons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Oral	LD50	>15000 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rab)	
Inhalative	LC50 / 4 h	4951 mg/m3 (rat)	
67-56-1 m	67-56-1 methanol		
Oral	LD50	5628 mg/kg (rat)	
Dermal	LD50	15800 mg/kg (rabbit)	
· Primary ir	· Primary irritant effect:		
. Skin corro	. Skin corrosion/irritation No irritant affect		

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50 / 24 h 150 mg/l (daphnia magna)

(Contd. on page 7)

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

	(Contd. of page
EC50 / 48 h 7.4 mg/l (daphnia magna)	
LC50/96 h 3.77 mg/l (fish)	
64742-82-1 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%	5)
EC50 / 48 h 10-22 mg/l (daphnia magna)	
EC50 / 72 h 4.6-10 mg/l (algae)	
LC50 / 96 h 10-30 mg/l (fish)	
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50/96 h > 100 mg/l (fish)	
Ecotoxical effects: Remark: Harmful to fish Additional ecological information: General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms 12.5 Results of PBT and vPvB assessment	

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

14.1 UN-Number	
ADR, ADN, IMDG	Void
IATA	UN1993
14.2 UN proper shipping name	
ADR, ADN, IMDG	Void
IATA	FLAMMABLE LIQUID, N.O.S. (TURPENTINE
	SUBSTITUTE, Solvent naphtha (petroleum), light arom.)

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

		(Contd. of page ?
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG		
· Class	Void	
· IATA		
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group		
· ADR, IMDĞ	Void	
·IATA	III	
· 14.5 Environmental hazards:		
• Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Anne	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN ''Model Regulation'':	-	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

1	΄ κειεναπι μπι	uses
	H225	Highly flammable liquid and vapour.
	H226	Flammable liquid and vapour.
	H301	Toxic if swallowed.
	H304	May be fatal if swallowed and enters airways.
	H311	Toxic in contact with skin.
	H331	Toxic if inhaled.
	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H370	Causes damage to organs.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H411	Toxic to aquatic life with long lasting effects.
	R10	Flammable.
	R11	Highly flammable.
	R11 R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
	R37	Irritating to respiratory system.
		Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if
	10 // 20/ 2 1/ 20	swallowed.
	R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
		(Contd. on page 9)

GB -

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 51

Revision: 02.06.2015

Trade name: MOTIP BITUMEN BASED UNDERCOATING

R51/53 R65 R66 R67	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. issuing MSDS: R&D legislation and regulatory advisor K. Smedeman
R66 R67	Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. issuing MSDS: R&D legislation and regulatory advisor
R67	Vapours may cause drowsiness and dizziness. issuing MSDS: R&D legislation and regulatory advisor
	issuing MSDS: R&D legislation and regulatory advisor
_	
· Department	
-	
· Abbreviation	ns and acronyms:
	t international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
0	ransport of Dangerous Goods by Rail)
	ional Civil Aviation Organisation
	uropéen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dat	ngerous Goods by Road)
	tional Maritime Code for Dangerous Goods
	onal Air Transport Association
	Harmonised System of Classification and Labelling of Chemicals
	bean Inventory of Existing Commercial Chemical Substances
	pean List of Notified Chemical Substances
	Abstracts Service (division of the American Chemical Society)
LD50: Lethal de	oncentration, 50 percent
	lammable liquids, Hazard Category 2
	lammable liquids, Hazard Category 3
	cute toxicity, Hazard Category 3
	ecific target organ toxicity - Single exposure, Hazard Category 1
STOT SE 3: Spe	ecific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Spe	ecific target organ toxicity - Repeated exposure, Hazard Category 1
STOT RE 2: Spe	ecific target organ toxicity - Repeated exposure, Hazard Category 2
	piration hazard, Hazard Category 1
	c 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
	c 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3
• * Data comp	pared to the previous version altered.