

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MOTIP ANTI CORROSION PRIMER

· Article number: 090106

 $\cdot$  1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

 $\cdot$  Application of the substance / the mixture Preparation

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

• Further information obtainable from: QHSE Department • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

**SECTION 2: Hazards identification** 

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS07

R36:

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chron	ic 3 H412	Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Irritating to eyes.

F+; Extremely flammable

*R12: Extremely flammable.* 

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. (Contd. on page 2) Page 2/11

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

## Trade name: MOTIP ANTI CORROSION PRIMER

			(Contd. of page 1
	Pressurised container.		
	cotising effect.		
	ion system:		, <u>, , , , , , , , , , , , , , , , , , </u>
The classij data.	ication is according to	the latest editions of the EU-lists, and extended b	by company and literature
2.2 Label			
		on (EC) No 1272/2008	
		elled according to the CLP regulation.	
Hazard pi	nograms		
	$\mathbf{A}$		
<b>( ())</b>			
V	$\mathbf{v}$		
GHS02	GHS07		
Signal wo	<b>d</b> Danger		
	termining component	s of labelling:	
acetone			
butan-1-ol <b>Hazard sta</b>			
		a gamagal Programigad containon May hungt if ha	atad
<i>п222-п22</i> <i>Н319</i>		e aerosol. Pressurised container: May burst if hea	aiea.
нзт9 Н336	Causes serious eye i May cause drowsine		
нзэо H412			
		ife with long lasting effects.	
	nary statements	G abilduar	
P102	Keep out of reach of		
P260	Do not breathe spra		No on the
P210 P251		nt, hot surfaces, sparks, open flames and other ign	ution sources. No smoking.
P211	Do not pierce or bu	open flame or other ignition source.	
		it. Do not expose to temperatures exceeding 50 °C	C/122 °F
P501		container in accordance with local regulations.	C/122 T.
	information:	container in accortance with local regulations.	
	0	cause skin dryness or cracking.	
		<i>produce an allergic reaction.</i>	
2.3 Other		produce an anergie reaction.	
	PBT and vPvB assess	ment	
•	applicable.		
	applicable.		
<b>SECTIO</b>	N 3: Composition	information on ingredients	
	cal characterisation:		
-	•	es listed below with nonhazardous additions.	
Dangerou	s components:		
		acetone	25-50%
CAS: 67-6	200-662-2	🗙 Xi R36	
EINECS: 2		E D 1 1	
EINECS: 2 Index num	ber: 606-001-00-8	<b>●</b> <i>F R</i> 11	
EINECS: 1 Index num			
EINECS: 1 Index num	ber: 606-001-00-8		

(Contd. on page 3)

GB –

Page 3/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

# Trade name: MOTIP ANTI CORROSION PRIMER

CAS: 74-98-6	propane	ntd. of pag 10-12.5
EINECS: 200-827-9	F + R12	
Index number: 601-003-00-5	🔞 Flam. Gas 1, H220	
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas C, H280	
CAS: 1330-20-7	xylene	5-10%
EINECS: 215-535-7	Xn R20/21	5 107
Index number: 601-022-00-9	× Xi R38	
Reg.nr.: 01-2119488216-32-xxxx		
Reg. III .: 01 2119400210 52 MMA	<b>(</b> ) Flam. Liq. 3, H226	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 106-97-8	butane	5-10%
EINECS: 203-448-7	<b>b</b> F+ R12	
Index number: 601-004-00-0	🚸 Flam. Gas 1, H220	
Reg.nr.: 01-2119474691-32-xxxx	Press. Gas C, H280	
CAS: 75-28-5	isobutane	5-10%
EINECS: 200-857-2	▶ F+ R12	
Index number: 601-004-00-0	🐼 Flam. Gas 1, H220	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-10%
EINECS: 203-603-9	R10	/
Index number: 607-195-00-7	🛞 Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-xxxx		
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	2.5-5%
EINECS: 265-198-5	$\mathbf{X}$ Xn R65	
Index number: 649-424-00-3	N R51/53	
Reg.nr.: 01-2119494196-28-xxxx		
0	🗞 Asp. Tox. 1, H304	
CAS: 100-41-4	ethylbenzene	1-2.5%
EINECS: 202-849-4	$\mathbf{X}$ Xn R20	1 210 /
Index number: 601-023-00-4	F R11	
Reg.nr.: 01-2119489370-35-xxxx		
	STOT RE 2, H373; Asp. Tox. 1, H304	
	Acute Tox. 4, H332	
CAS: 71-36-3	butan-1-ol	1-2.5%
EINECS: 200-751-6	Xn R22	1 2.37
Index number: 603-004-00-6	Xi R37/38-41	
Reg.nr.: 01-2119484630-38-xxxx		
	🛞 Flam. Liq. 3, H226	
	Eye Dam. 1, H318	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-	
	H336	
CAS: 7779-90-0	trizinc bis(orthophosphate)	0.1-19
EINECS: 231-944-3	₩ N R50/53	
Index number: 030-011-00-6	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119485044-40-xxxx	· · · · · · · · · · · · · · · · · · ·	
CAS: 96-29-7	2-butanone oxime	0.1-19
EINECS: 202-496-6	Xn R21-40	J.1 1/
Index number: 616-014-00-0	Xi R41	
Reg.nr.: 01-2119539477-28-xxxx	Xi R43	
	Carc. Cat. 3	
	& Carc. 2, H351	
	Eye Dam. 1, H318	
	Acute Tox. 4, H312; Skin Sens. 1, H317	
		ntd. on pag

Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

#### Trade name: MOTIP ANTI CORROSION PRIMER

• Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. of page 3)

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Keep away from ignition sources.
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.

*Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.* 

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• *Requirements to be met by storerooms and receptacles:* Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

(Contd. on page 5)

Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

(Contd. of page 4)

## Trade name: MOTIP ANTI CORROSION PRIMER

- *Further information about storage conditions: Protect from heat and direct sunlight.*
- 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 67-64-1 acetone WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm 1330-20-7 xylene WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV 106-97-8 butane WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) 108-65-6 2-methoxy-1-methylethyl acetate WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm Long-term value: 441 mg/m<sup>3</sup>, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm Sk · Ingredients with biological limit values: 1330-20-7 xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes. Avoid contact with the eyes and skin. · Respiratory protection: Not required. · Protection of hands: Not required.
  - *Material of gloves* Not required.

· Penetration time of glove material Not required.

(Contd. on page 6)

<sup>-</sup> GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

(Contd. of page 5)

# Trade name: MOTIP ANTI CORROSION PRIMER

· Eye protection:



\*

Tightly sealed goggles

# SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	$<0 \ ^{\circ}C \ (< 32 \ ^{\circ}F)$
-	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	333 °C (631 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	0.82 g/cm <sup>3</sup> (6.843 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	76.0 %
EU-VOC:	622.8 g/l
EU-VOC in %:	75.95 %
Solids content:	24.6 %

Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

(Contd. of page 6)

Trade name: MOTIP ANTI CORROSION PRIMER

• 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· 10.1 Reactivity

\*

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

67-64-1 ac	etone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	20000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	39 mg/m3 (rat)	
1330-20-7	xylene		
Oral	LD50	3523 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	22.1 mg/m3 (rat)	
106-97-8 b	utane		
Inhalative	LC50/4h	658000 mg/m3 (rat)	
108-65-6 2	-methoxy-1	-methylethyl acetate	
Oral	LD50	8532 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	35.7 mg/m3 (rat)	
100-41-4 е	thylbenzen	,	
Oral	LD50	3500 mg/kg (rat)	
Dermal	LD50	17800 mg/kg (rabbit)	
71-36-3 bu	tan-1-ol		
Oral	LD50	2292 mg/kg (rat)	
Dermal	LD50	3430 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	17.76 mg/m3 (rat)	
7779-90-0	trizinc bis(e	orthophosphate)	
Oral	LD50	522 mg/kg (mouse)	
		>5000 mg/kg (rat)	
96-29-7 2-	butanone o.	<i>sime</i>	
Oral	LD50	2528 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50 / 4 h	20 mg/m3 (rat)	
Primary ir	ritant effect		

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

### Trade name: MOTIP ANTI CORROSION PRIMER

- Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

# SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:				
67-64-1 acetone				
EC50 / 48 h	8800 mg/l (daphnia magna)			
LC50 / 48 h	2262 mg/l (daphnia magna)			
LC50 / 96 h (static)	5540 mg/l (fish)			
1330-20-7 xylene				
EC50 / 48 h	7.4 mg/l (daphnia magna)			
LC50 / 96 h	13.5 mg/l (fish)			
108-65-6 2-methoxy-1-methylethyl acetate				
EC50	408 mg/l (daphnia magna)			
71-36-3 butan-1-ol	71-36-3 butan-1-ol			
EC50 / 48 h	1328 mg/l (daphnia magna)			
EC50 / 72 h	8500 mg/l (algae)			
LC50 / 96 h	1376 mg/l (Pimephales promelas)			
7779-90-0 trizinc bis(orthophosphate)				
EC50 / 48 h	0.04 mg/l (daphnia magna)			
EC50 / 72 h	0.136 mg/l (algae)			
LC50 / 96 h	0.14 mg/l (fish)			

· 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

- Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

(Contd. of page 7)

GB

Page 9/11

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

(Contd. of page 8)

# Trade name: MOTIP ANTI CORROSION PRIMER

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport informat	lon	
14.1 UN-Number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class Label	2.1 2.1	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F-D,S-U	
14.7 Transport in bulk according to Anne		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
Transport officer	Not permitted as Excepted Quantity	
Transport category Tunnel restriction code	2 D	
IMDG	IL	
Limited quantities (LQ) Excepted quantities (EQ)	TL Code: E0	
Excepted quantities (EQ)	Not permitted as Excepted Quantity	
		Contd. on page 1

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

(Contd. of page 9)

Trade name: MOTIP ANTI CORROSION PRIMER

· UN ''Model Regulation'':

UN1950, AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- *R12 Extremely flammable.*
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R21 Harmful in contact with skin.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- *R40 Limited evidence of a carcinogenic effect.*
- R41 Risk of serious damage to eyes.
- *R43* May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65 Harmful: may cause lung damage if swallowed.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67* Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: R&D legislation and regulatory advisor

· Contact: Mr. K. Smedeman

(Contd. on page 11)

GB

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 30

Revision: 02.06.2015

## Trade name: MOTIP ANTI CORROSION PRIMER

	(Contd. of page 10
• Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regula	ations Concerning the
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concer	rning the International
Carriage of Dangerous Goods by Road)	-
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
Flam. Gas 1: Flammable gases, Hazard Category 1	
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1	
Press. Gas C: Gases under pressure: Compressed gas	
Flam. Liq. 2: Flammable liquids, Hazard Category 2	
Flam. Liq. 3: Flammable liquids, Hazard Category 3	
Acute Tox. 4: Acute toxicity, Hazard Category 4	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2	
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1	
Carc. 2: Carcinogenicity, Hazard Category 2	
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2	
Asp. Tox. 1: Aspiration hazard, Hazard Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3	
* Data compared to the previous version altered.	